TOSHIBA

E-STUDIO2309A

Compact. Efficient. Economical.







DUPLEX





COLOUR SCAN

COPY SPEED





Increased productivity

Offers a wide range of paper handling options to satisfy the varying needs of users.



Colour Scan and Scan to USB

Besides having the capability of Colour Scan, users can also enjoy the convenience of scanning directly to USB drive.

Department codes

Administrators can manage printing cost by tracking the print volume of departments and users, limiting unauthorised usage through this simple security management.

Mobile Printing

Printing is even more hassle-free now! Simply connect and print directly from your mobile phone or tablet.

*With PS option on e-STUDI02309A/2809A







SPECIFICATION for		e-STUDIO2309A	
GENERAL ———			
Copying/Printing Process		Indirect electrostatic photographic method	
Print & Copy Speed		23cpm	
Warm-up Time		Approx. 18 seconds Drawer: A3/A5-R (64 - 80gsm)	
Paper Size & Weight		Drawer: A3/A5H (64 - 9)gm) Stack Feed Bypass: A3/A5H (52 - 216gsm)	
Paper Capacity		Drawer: 250 sheets	
Paper Capacity		Stack Feed Bypass: 100 sheets	
Max. Paper Capacity		1700 sheets	
Paper Exit		Face down/Inner exit (100 sheets)	
Processor		Cortex AB 500MHz	
Memory		512MB	
Dimensions		W575 x D540 x H402 (mm)	
Weight (Approx.)		27kg	
Power Consumption		1.5kW (220-240V)	
Operation Noise		64.75dB[A]	
Special Features		Auto Sleep Mode, Auto Energy Saver	
COPY —			
Max. Original Size		A3	
Resolution		2400dpi x 600dpi (with smoothing)	
Multiple Copy Qty		1-999/Ten key input	
First Copy		Less than 6.4 seconds (A4 size from 1st drawer, 100%)	
Zoom		25% to 400% (1% Increment)	
Copy Mode		Text, Text/Photo(Default), Photo, Background Erase	
Image Density Control		Automatic / Manual (9 Steps)	
PRINT —			
PRIIVI Resolution		24004si u COO4si (sith amentina)	
Page Description Language		2400dpi x 600dpi (with smoothing) PCL6 (PCL, XL), PCL5c, PCL5c, PS (Option)	
Operating Systems		Vindows Vista SP2 (32/64 bit)	
Operating Systems		Windows 7 SP1 (32/64 bit) (SP1 Recommended)	
		Windows 8.1 (32/64 bit)	
		Windows 10 (32/64 bit)	
		Windows Server 2008 SP2 (32/64 bit) Windows Server 2008 R2 SP1 (64 bit)	
		Windows Server 2012 /R2 (64 bit)	
		Mac 0S 10.6, 10.7.4, 10.8, 10.9, 10.10, 10.11	
		UNIX, Linux (CUPS)	
Interface		10/100 BaseT, USB 2.0/Hi Speed	
Network Protocol		TCP/IP (IP v4/IP v6) NetBIOS over TCP/IP	
Print Protocol		LPR/LPD, Port 9100 (bi-directional), IPP ver1.1	
Print Function		Toner Save Mode, Watermark, Multiple Pages Per Sheet	
SCAN			
Resolution		600 x 600dpi	
Scan Speed		Up to 25spm	
Scan Modes		B&W, Greyscale, Colour	
File Formats		B&W: TIFF-Multi/Single page, PDF-Multi/Single-Page	
		Greyscale: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page	
		Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page	
Scan Agent		Scan to USB, Remote TWAIN	
		Scan to File (SMB/FTP), Scan to Email	
FAX (OPTION) —			
		Super 63, 63	
Compatibility			
Data Compression Method Modem Speed		JBIG, MMR, MR, MH 33.6kbps - 2.4Kbps (Auto Fallback)	
Transmission Speed		33.6kbps - 2.4Kbps (Auto Fallback) Approx. 3 sec.	
Broadcast Transmission		Approx. 3 sec. Max. 32 Groups, 220 destinations per job	
E. Judouse il alisinissiUII		тип. С. 6. обра, е. С. обощновать ры ро	
OPTIONS —			
Document Feeder (RADF)	MR-3029	✓	
Platen Cover	KA-2507PC	<u></u>	
Paper Feed Unit	MY-1043	<u> </u>	
Desk	MH-2506	✓	
Harness Kit for	GQ-1131	·	
Coin Controller			
Auto Duplex Unit	MD-0107	N.A (Standard)	
Paper Feed Pedestal	KD-1039	✓	
Drawer Module	MY-1044	<u>V</u>	
FAX Kit	GD-1360	<u> </u>	
Wireless LAN Module	GN-1080	V	
PS module + 1GB memory	GA-1340L	<u> </u>	TSP Version 1.0
(es2309A) PS module + 1GB memory	CA 4040U		Driven by
(es2809A)	GA-1340H	✓	الأران النبيان وي
(GPCOODA)			







Corporate Office
Ranks Business Centre (3rd Floor), KA 218/1 Pragati Sarani, Kuril, Dhaka 1229.
Hotline: 09611858585, Tel: 8418523 | Fax: 8417589 | E-mail: info@iomltd.com



