

TOSHIBA

e-STUDIO2802AM

Small footprint,
big results.



COPY



PRINT



A3



DUPLEX



COLOUR
SCAN




28
BW CPM
COPY
SPEED



TOGETHER
INFORMATION

A3 and A4 Monochrome copy-based MFP



A compact machine which supports not only A4 paper, but also prints on A3 paper using paper feed from the bypass tray.


Ease of Use



Intuitive and efficient 4-line LCD info panel and special feature buttons which support ID Card Copy & Original Mode selection.

High Image Quality


Outstanding reproduction of grey shades. The Background Erase mode removes background colours when copying originals.



Background Erase

Reduced Cost

Reduced paper and print cost using 2-in-1/4-in-1 function.



SPECIFICATION for		e-STUDIO2802AM
GENERAL		
Copying/Printing Process	Indirect electrostatic photographic method	
Print & Copy Speed	28cpm	
Warm-up Time	Approx. 18 seconds	
Paper Size & Weight	Drawer: A4 (64 - 80gsm) Stack Feed Bypass: A3/A5-R (52 - 216gsm)	
Paper Capacity	Drawer: 250 sheets Stack Feed Bypass: 50 sheets	
Max. Paper Capacity	300 sheets	
Paper Exit	Face down/Inner exit (50 sheets)	
Processor	Cortex A8 500MHz	
Memory	512MB	
Dimensions	W390 x D540 x H505 (mm)	
Weight (Approx.)	26.5kg	
Power Consumption	1.5KW (220-240V)	
Operation Noise	64.75dB(A)	
Special Features	Auto Sleep Mode, Auto Energy Saver	
COPY		
Max. Original Size	A4 (Via Platen) A3 (Via RADF)	
Resolution	2400dpi x 600dpi (with smoothing)	
Multiple Copy Qty	1-999	
First Copy	Less than 6.4 seconds (A4 size from 1st drawer, 100%)	
Zoom	25% to 400% (1% Increment)	
Copy Mode	Text, Text/Photo (Default), Photo, Background Erase	
Image Density Control	Automatic/Manual (9 Steps)	
PRINT		
Resolution	2400dpi x 600dpi (with smoothing)	
Page Description Language	PCL6 (PCL_XL), PCL5e, PCL5c	
Operating Systems	Windows Vista SP2 (32/64 bit) Windows 7 SP1 (32/64 bit) (SP1 Recommended) Windows 8/8.1 (32/64 bit) Windows Server 2008 SP2 (32/64 bit) Windows Server 2008 R2 SP1 (64 bit) Windows Server 2012/R2 (64 bit) Mac OS 10.6, 10.7, 10.8, 10.9, 10.10 UNIX, Linux (CUPS)	
Interface	Standard: 10/100 BaseT, USB 2.0/Hi Speed	
Network Protocol	TCP/IP (IP v4/IP v6) NetBIOS over TCP/IP	
Print Protocol	LPR/LPD, Port 9100 (bi-directional), IPP ver1.1	
Print Function	Toner Save Mode, Watermark, Multiple Pages Per Sheet	
SCAN		
Resolution	600 x 600dpi	
Scan Speed	Up to 25spm	
Scan Modes	BSW, Greyscale, Colour	
File Formats	BSW: TIFF-Multi/Single page, PDF-Multi/Single-Page Greyscale: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page	
Scan Agent	Scan to USB, Remote TWAIN, Scan to File (SMB/FTP), Scan to Email	
OPTIONS		
Wireless LAN Module	GN-1080	✓
Harness Kit for Coin Controller	GQ-1131	✓
Front Cover Customisation Kit	KK-2505	✓
Desk	MH-2505	✓

TSP Version 1.0

Distributed by

Microsoft and Windows® are registered trademarks of Microsoft Corporation in the United States and/or other countries. All other brand and/or product names are trademarks of their respective owners. This brochure was compiled based on information that was accurate prior to product launch. Product design and specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. 1GB is equivalent to 1 billion bytes. Warm-up time and print speed may vary depending on the operating environment. ©2015 TOSHIBA TEC CORPORATION All rights reserved. As an ENERGY STAR Partner TOSHIBA TEC CORPORATION has determined that this multifunction device model meets the ENERGY STAR guidelines for energy efficiency.



International Office Machines Ltd.

Corporate Office
Ranks Business Centre (3rd Floor), KA 218/1 Pragati Sarani, Kurl, Dhaka 1229.
Hotline: 09611858585, Tel: 8418523 | Fax: 8417589 | E-mail: info@iomltd.com

Branches
Motijheel- 7126124, 9564618 | Chittagong- 613705, 638606, 01714084429
Bogra- 66435, 65531, 01711890615 | Khulna- 732372, 01716749065 | Sylhet- 712240

