

TOSHIBA

B-EV4T DESKTOP PRINTER

Product brochure

- ▶ For fast, on-demand labelling and ticketing direct from your desktop, look no further than the trustworthy B-EV4 range from Toshiba.
- ▶ With market-leading features, exceptional build quality and reliability, produce professional labels quickly and easily at the touch of a button.



SPECIFICATIONS

General

Print Method	B-EV4T GS/TS: Direct thermal/Thermal transfer
Printhead	Flat head
Dimensions (W x D x H)	B-EV4T GS/TS: 198 x 258 x 173 mm
Weight	B-EV4T GS/TS: 2.4 kg
User interface	Single LED (colours: green, amber, red)
Operating Temperature / Humidity	5°C to 40°C / 25-85% non-condensing relative humidity (RH)
Storage Temperature / Humidity	-40°C to 60°C / 10-90% non-condensing relative humidity (RH)
Power supply	AC 100 to 240V, 50/60 Hz AC adapter

Print

Resolution	GS/TS: 203/300 dpi (8/11.8 dots/mm)
Sensor	Reflective, Transmissible
Maximum Print Speed	GS/TS: 127/101.6 mm/second (5/4 ips)
Maximum Print Width	GS/TS: 108/106 mm
Print Length	<u>B-EV4T-GS</u> Batch: 8-997 mm Cut: 23.4-993 mm Peel-off: 23.4-150.4 mm

B-EV4T-TS

Batch: 8-455.2 mm
Cut: 19.4-451.2 mm
Peel-off: 23.4-150.4 mm

Barcodes	UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Postnet, RM4SCC, KIX-Code, GS1 Databar
2D Codes	Data Matrix, PDF 417, Maxicode, QR Code, Micro PDF 417
Fonts	Bitmap font, Outline font, Price font, TTF

Ribbon

Ribbon Width	33.8 to 110 mm
Ribbon Core Size	12.7 mm
Fixed Core Length	110 mm
Max. Ribbon Length	110 m
Max. Ribbon Diameter	40 mm

Media

Alignment	Centred
Backing Paper Width	25.4-112 mm
Label Thickness	0.06-0.19 mm
Inner Media Core Diameter	25.4 - 38.1 mm (optional: 76.2 mm)
Outer media Roll Diameter	Max. 127 mm (214 mm with external media stand)
Media Type	Labels, Receipts, Coreless media
Media Format	Roll, Fanfold

Software & Connectivity

Emulation	ZPL II, EPL, DPL, IPL
Printer Driver	Windows 10/8/7/Vista (32/64 bit), Windows Server 2012/Server 2008 (32/64 bit)
Interface	RS-232C (max. 115,200 bps), Centronics (SPP), USB 2.0 (Full Speed), LAN 10/100 Base, SD card
Language Mode	TPCL
Label Software	BarTender UltraLite

Options

Common	Full cutter module, Partial cutter module. Peel-off module, External 203 mm OD media stand, Keyboard unit (KB-75-QM-R), Power cable tray
---------------	--



Together Information is Toshiba's vision for how people and organisations create, record, share, manage and display ideas and data. It is based on our belief that the most successful organisations are those that communicate information in the most efficient way. We make that possible through an integrated portfolio of industry-specific solutions, all of which reflect Toshiba's commitment to the future of the planet.

About Toshiba Tec

Toshiba TEC Corporation is a leading provider of information technology, operating across multiple industries - ranging from retail, education and business services to hospitality and manufacturing. With headquarters in Japan and over 80 subsidiaries worldwide, Toshiba TEC Corporation helps organisations transform the way they create, record, share, manage and display information.

For more information please contact us:
Toshiba TEC Singapore Pte Ltd
2 Ang Mo Kio Street 62 Singapore 569138
Tel : (65) 6481 9488, Fax : (65) 6481 2385

Distributed by

International Office Machines Ltd.

Corporate Office
Ranks Business Centre (3rd Floor), KA 218/1 Pragati Sarani, Kuril, Dhaka 1229.
Hotline: 0961 1858585, Tel: 8418523 | Fax: 8417589 | E-mail: info@iomltd.com

Branches
Motijheel- 9564618, 01816256418 | Chattogram- 613705, 01714084429
Bogura- 65531, 01711890615 | Khulna- 732372, 01716749065 | Sylhet- 712240, 01711160285



Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation.

Copyright ©2018 TOSHIBA TEC. BR_B-EV4 series_2018

