ZD230 4-Inch Value Desktop Printer

Get more: Extra features, quality construction, exceptional value

Not all printers are created equally, especially basic models. To reduce costs, value printers are often constructed using less expensive components and fewer features. Many fail to perform under more demanding duty cycles, create delays and downtime for repairs, and require replacement after only a few years of use. Instead of conserving budget, customers are left with greater expense and hassle. Zebra does it differently. Meet the exception. The ZD230 desktop printer gives you extra features and reliable operation at an affordable price—both at the point of purchase and across the entire lifecycle. Engineered with Zebra quality, it boasts a dual-wall construction. And, it offers wireless connectivity for networked, remote printing. Built to last for years, the ZD230 provides an outstanding return on your investment.



Get Printing Quickly

The ZD230 is simple to install and begin printing—right out of the box. Easily replace legacy printers using ZPL, EPL or non-Zebra command languages. USB, Ethernet, Wi-Fi and Bluetooth® connectivity options enable universal interoperability. The ZD230 can accommodate a 300 M ribbon roll to lengthen the time between media changes. And, Zebra's OpenACCESS[™] clamshell design expedites media replacement. It's also ENERGY STAR® quali ed to reduce your operational expenses.

Just the Features You Need

This 4-inch printer produces labels quickly, up to 6" per second, to keep your work ows moving. Increased memory allows you to store more fonts and graphics. A single LED indicator and single button for feed/pause make it easy to operate and identify printer status. Choose from direct thermal or thermal transfer models, and add an optional factory-installed peeler or cutter.The ZD230 features Print DNA Basic, a core set of software applications and capabilities to deliver a cost-e ective and dependable print experience. It is ideal for use in transportation and logistics, light manufacturing, retail and healthcare applications to print a variety of tickets, tags, passes, labels and receipts.

Backed by Zebra's Worldwide Service and Support Access repair support services, live-agent technical support and software support quickly anywhere around the globe through Zebra and its trusted network of more than 10,000 partners. Zebra OneCare[™] provides enhanced coverage that exceeds standard warranty for normal wear and tear, priority repair turnaround times at the depot and more—all for a tiny fraction of the cost of a single repair.

Consistently Exceptional Zebra Certi ed Supplies Printing supplies can impact everything from printhead lifespan to operational e ciency. That's why we design, produce and rigorously pretest our own line of thermal printing supplies to ensure consistent, optimized performance in your Zebra printer—and peace of mind for you. For industry-leading quality, service and thermal printing expertise, choose Zebra Certi ed Supplies.



Get more from your investment: Quality, reliability and extra features For more information, visit www.zebra.com/zd230



ZD230 Specifications

Standard Features		Media Sensors	Movable black mark sensor, limited range from
Single button for feed/pause - • USB connectivity - • OpenACCESS™ for easy media loading - • Dual-wall frame construction - • ENERGY STAR qualified - • ZebraDesigner Essentials - easy label design tool free at - www.zebra.com/zebradesigner - • Two-year standard warranty -			center to left side Fixed o -center gap sensor
		Firmware	ZPL II; EPL 2; XML
		Media and Ribbon Characteristics	
		Maximum Label Length	39.0 in./991 mm
		Media Width	1.00 in. / 25.4 mm to 4.4 in. / 112 mm
		Media Roll Size	5.00 in./127 mm outer diameter Core inner diameter: 0.5 in. (12.7 mm) and 1.0 in. (25.4 mm) standard, 1.5 in. (38.1 mm)
Physical Characterist Dimension	TICS Thermal Transfer: 10.5 in. L x 7.75 in. W x 7.5 in. H 267 mm L x 197 mm W x 191 mm H Direct Thermal 8.6 in. L x 6.9 in. W x 5.9 in. H 220 mm L x 176 mm W x 151 mm H	Thickness	0.003 in. (0.08 mm) min.; 0.0075 in. (.1905 mm) max. (tear-omode only)
		Media Types	Roll-fed or fan-fold, die cut or continuous with or without black mark, tag stock, continuous receip paper, and wristbands
Weight	2.5 lbs./1.1 kg	Ribbon Outside Diameter	2.6 in./ 66 mm (300 m); 1.34 in./ 34 mm (74 m)
Printer Speci catio	ons	Maximum Ribbon	
Resolution*	203 dpi/8 dots per mm	Length	984 ft. (300 m)
Memory	128 MB Flash; 128 MB SDRAM	Ribbon Ratio	1:4 media to ribbon (300 m) 1:1 media to ribbon (74 m)
Maximum Print Width	4.09 in./104 mm for 203 dpi	Ribbon Width	1.33 in./ 33.8 mm ~ 4.3 in./ 109.2 mm
Programmable Print Speed	6 in./152 mm per second or 4 in./102 mm per second	Ribbon Core I.D.	300 Meter ribbon 1 in./ 25.4 mm 74 Meter ribbon 0.5 in./ 12.7 mm

Markets and Applications

- Light Manufacturing
- roduct labeling
- Asset management
- nventory management
- Vork-in-process racking
- ansportation d Logistics
- hipping labels
- ross docking
- tail
- rice labeling
- eceipt printing
- althcare
- atient identi cation

ZD230 Specifications

Operating Characteri	stics
Operating Temp.	40° to 105° F/4.4° to 41° C
Storage Temp.	-40° to 140° F/-40° to 60° C
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Electrical	Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz; ENERGY STAR quadd
Operations and Acces	ssories
Media Handling	Factory installed peeler or cutter
Communications	Factory-installed USB and Ethernet Factory-installed USB and Bluetooth 4.1 Factory-installed USB 802.11 ac Wi-Fi and Bluetooth 4.1
Real Time Clock	None
Keyboard Display Unit	No serial port, thus no KDU/ZKDU
Fonts/Graphics/Symb	pologies
Bar Code Ratios	2:1 and 3:1
1D Bar Codes	Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-or 5-digit extensions, Plessey, Postnet, Standard 2-c 5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar and Planet Code
2D Bar Codes	Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, MicroPDF, Aztec
Fonts and Graphics	16 resident expandable ZPL II bitmap fonts Two resident scalable ZPL fonts Five resident expandable EPL2 fonts Native open-type font support Unicode compliant for multi-language, on demar thermal printing 50 MB user available non-volatile memory, 8 MB user available SDRAM

available directly from	er up and running with genuine Zebra printer suppl 1 Zebra.
Regulatory	
Class B, ICES-003, FCC EN 62311, cTUVus	Class B, EN55024, EN61000-3-2, EN61000-3-3, FC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 89 ck, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS,
Recommended Servi	ices
Zebra OneCare SV	
Operating System	
Link-OS Basic printer of	operating system
Print DNA Software	
This printer is suppor capabilities.	ted by a core set of Print DNA Basic applications a
	ted by a core set of Print DNA Basic applications a Enhances out-of-the-box experience by enabling quick and easy printer comuration
capabilities.	Enhances out-of-the-box experience by enabling
capabilities. Zebra Setup Utilities ZebraDesigner	Enhances out-of-the-box experience by enabling quick and easy printer coguration Makes designing and printing industry-standard and compliant labels simple, includ keg or
capabilities. Zebra Setup Utilities ZebraDesigner Essentials Emulations	Enhances out-of-the-box experience by enabling quick and easy printer coguration Makes designing and printing industry-standard and compliant labels simple, includ ing or variable data On-printer apps allow Zebra printers to use legac languages normally associated with other printer



INTERNATIONAL OFFICE MACHINES LIMITED

Corporate Office Ranks Business Centre (3rd Floor), KA 218/1 Pragati Sarani, Kuril, Dhaka 1229. Hotline: 09611858585,Tel: 8418523 |Fax: 8417589 | E-mail: info@iomltd.com

Branches

 Chattogram 6/32, Zilla Parishad Super Market
 101714-168943

 Bogura Saptapadi Market, Bogra
 101711-890615

 Khulna 65, Ahsan Ahmed Road
 101716-749065

 Sylhet-6/03
 Karimullah Market, Bandar Bazar
 101711-160285



NA and Corporate Headquarters +1 800 423 0442 inquiry4@zebra.com Asia-Paci c Headquarters +65 6858 0722 contact.apac@zebra.com EMEA Headquarters zebra.com/locations contact.emea@zebra.com Latin America Headquarters +1 786 245 3934 la.contactme@zebra.com

ZEBRA and the stylized Zebra head are trademarks of Zebra Technologies Corporation, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. ©2020 Zebra Technologies Corporation and/or its a Part number: SS-ZD230 05/11/2021