

TOSHIBA

e-STUDIO™ 2518A



- Black & White Multifunction Printer
- 25 PPM
- Medium/Large Workshop
- Copy, Print, Scan, Fax
- Secure MFP
- Solutions Ready

TOGETHER
INFORMATION

e-STUDIO™ 2518A

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/LED Printing/ Heat Roller Fusing
Display	10.1" Colour WSVGA Touch Screen Tilting Display
Copy Speed	25 PPM (A4)
First Copy Out	4.3 Seconds
Warm-Up Time	Approx. 20 Seconds
Copy Resolution	2,400 x 600 dpi with Smoothing
Stack Feed Bypass	100 x 148 mm to A3, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 1,200 Sheets/Max. 3,200 Sheets
Original Feed	Optional 300-Sheet DSD/ or 100-Sheet RADF
Scan Speed & Weights	DSD/ Scan: Up to 240 IPM Duplex, 120 IPM Simplex, Simplex: 35 - 209 gsm, Duplex: 35 - 209 gsm RADF Scan: Up to 73 IPM, Simplex: 35 - 157 gsm, Duplex: 50 - 157 gsm
Max. Original Size	A3
Paper Feed Sizes	Drawer 1: 550 Sheets- A5-R to A3 Drawer 2: 550 Sheets- A5-R to 320 x 460 mm Stack Feed Bypass: 100 Sheets- 100 x 148 mm to 320 x 460 mm, 305 x 1,200 mm Banner Opt. 550-Sheet Paper Feed Pedestal- A5-R to 320 x 460 mm Opt. 550-Sheet Drawer for PFP- A5-R to 320 x 460 mm Opt. Envelope Cassette for PFP- Approx. 60 Envelopes/550 Sheets - 16K-R to A4-R Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-A4 Only Standard: 550 Sheets x 2- 60 - 256 gsm Stack Feed Bypass: 100 Sheets- 52 - 256 gsm Opt. 550-Sheet Paper Feed Pedestal- 60 - 256 gsm Opt. 550 Sheets Drawer for PFP- 60 - 256 gsm Opt. Envelope Cassette for PFP- 60 - 256 gsm Opt. 2,000-Sheet Tandem LCF (Pedestal Type)- 64 - 105 gsm Standard Automatic Duplex Unit (60 - 256 gsm)
Paper Weights	Duplex Reproduction Ratio Max Duty Cycle Weight Approx. Dimensions Toner Yield Power Source Power Consumption CPU Memory Hard Disk Drive

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	25 Pages Per Minute (A4)
Print Resolution	600 x 600 dpi (1 bit) or 2,400 (Equivalence) x 600 dpi (with Smoothing), 1,200 x 1,200 dpi (2 bit) or 3,600 x 1,200 dpi (with Smoothing) PS 3
Operating Systems	Windows Server® 2008 R2, R2 SP1, 2008/SP2, Windows® 7,8,10, Windows Server® 2012/R2, Windows Server® 2016, Macintosh® (MacOS x 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13), Unix®, Linux® TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/S PX® for Novell® Environments, EtherTalk® for Macintosh Environments
Network Protocols	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed), Optional 802.11b/g/n, Wireless LAN, Optional Bluetooth
Interface	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple App Store or Google Play)
Wireless Device	TopAccess, e-Suite
Device Management	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Account Control Device), Login Name/Password (via Windows domain) or Login Name/ Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Security Features	User Authentication, On-Board Data Scramble Function, Scep®, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC 15408) * IEE E802.1X (Wired/Wireless),



Digital Signature for Client Utilities, Password Policy, Password Lock,
Password Expiration, Self Testing, Job Access Control,
Log Access Control for Job Log, Security Stamp Role Based Access Control,
Secure PDF, Digital Signature for firmware update, Integrity Check function,
Image Log, Card Authentication, NFC Authentication * Conformance with
HCD-PP v1.0 in High security mode.
ENERGY STAR® (V2.0), Blue Angel Mark (RAL UZ-205, MFD), Nordic Swan, RoHS
WHQL (Windows 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell, Citrix, SAP,
Airprint and Mopria

Environmental Standards Certification

Scan Specifications

Scan Speed	DSD/ Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour) RADF Scan: Up to 73 IPM (Monochrome or Colour)
Scan Modes	Standard: Full Colour, Auto Colour, Monochrome, Grayscale 600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
Scan Resolution	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Colour/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
File Formats	Colour/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations /Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Colour Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options			
DSD/	MR-4000-B	Data OverWrite Enabler	GP-1070
RADF	MR-3031-B	USB Hub	GR-1310
Platen Cover	KA-5005PC	Meta Scan Enabler	GS-1010
		IPsec Enabler	GP-1080
Additional Paper Options		Unicode Font Enabler	GS-1007
Paper Feed Pedestal	KD-1058-B	Embedded OCR Enabler	
Drawer Module	MY-1048-B	Single License	GS-1080
Envelope Cassette Option	MY-1049-B	Five Licenses	GS-1085
Large Capacity Feeder	KD-1059A4-B	Multi-Station Print Enabler	
		Single License	GS-1090
Finishing Options		Five Licenses	GS-1095
Inner Finisher	MJ-1042-B		
50-Sheets Staple Finisher	MJ-1109-B	Miscellaneous Options	
Saddle-Stitch Finisher	MJ-1110-B	Stand	MH-5005
Hole Punch Unit for MJ1042	MJ-6011	Accessory Arm	KK-2560
Hole Punch Unit for MJ1109/MJ1110	MJ-6105	Work Tray	KK-5005
Bridge Kit	KN-5005	Harness Kit for Coin Controller	GQ-1280
Job Separator	MJ-5014	Manual Pocket	KK-5008
Connectivity/Security Options			
Printer Scanner Enabler option	GM-2290		
FAX Unit/2nd Line for FAX Unit	GD-1370EU		
Wireless LAN/Bluetooth	GN-4020		
Accessory Tray	GR-1330		
Panel 10-Key Option	GR-1340		
Card Reader Holder	GR-1320		
4GB Memory Option	GC-1410		

Distributed by

Toshiba TEC Singapore Pte Ltd
2 Ang Mo Kio Street 62
Singapore 569138
Tel : (65) 6481 9488
Fax : (65) 6481 2385



TOSHIBA
Authorized Sole
Distributor

INTERNATIONAL OFFICE MACHINES LIMITED

Corporate Office
Ranks Business Centre (3rd Floor), KA 218/1 Pragati Sarani, Kuril, Dhaka 1229.
Hotline: 09611858585, Tel: 8418523 | Fax: 8417589 | E-mail: info@iomltd.com

Branches

Chattogram- 6/32, Zilla Parishad Super Market | 01714-168943
Bogura-Saptapadi Market, Bogra | 01711-890615
Khulna-65, Ahsan Ahmed Road | 01716-749065
Sylhet-6/03 , Karimullah Market, Bandar Bazar | 01711-160285