

# TOSHIBA

**e-STUDIO 3528A**

## Monochrome Multifunctional Printers

- > Up to 35 PPM
- > Compact Design
- > Advanced Security Features
- > Solutions Ready
- > Environmentally Friendly



**TOGETHER  
INFORMATION**

## MAIN SPECIFICATIONS

<b>Copy Process</b>	Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing
<b>Display</b>	10.1" Colour WSVGA Touch Screen Tilting Display
<b>Copy Speed</b>	35 ppm (A4)
<b>Warm-Up Time</b>	Monochrome: Less Than 4.3 Seconds From Powering on: Approx. 20 Seconds From Sleep & Low Power: Less Than 20 Seconds
<b>Copy Resolution</b>	600 x 600 dpi
<b>Stack Feed Bypass</b>	A3 - 100 x 148 mm, Envelope
<b>Multiple Copying</b>	Up to 999 Copies
<b>Paper Capacity</b>	Standard 1,200 Sheets/Max. 5,200 Sheets
<b>Original Feed</b>	300 - Sheet DSDf or DSDf with Double Feed Detection or 100 - Sheet RADf
<b>Scan Speed</b>	DSDf Scan: 70 ipm, (Monochrome or Colour), RADf Scan: 50 ipm
<b>Max. Original Size</b>	LD/A3
<b>Paper Feed Sizes</b>	Drawer 1: 550 Sheets, A3 - A5R Drawer 2: 550 Sheets, 320 x 460 mm to A5R Stack Feed Bypass: 320 x 460 mm to 100 x 148 mm Opt. 550 - Sheet Paper Pedestal - 320 x 460 mm to A5R Opt. 550 - Sheet Drawer for PFP - 320 x 460 mm to A5R Opt. Envelope Cassette for PFP - A4R, B5R, A5R, 16K-R Opt. 2,000 - Sheet Tandem LCF (Pedestal Type) - A4 Only Opt. 2,000 - Sheet External LCF - A4 Only
<b>Paper Weights</b>	Standard: 550 Sheets x 60 - 256 gsm Stack Feed Bypass: 100 Sheets x 60 - 256 gsm Opt. 550 - Sheet Paper Feed Pedestal x 60 - 256 gsm Opt. 550 - Sheets Drawer for PFP x 60 - 256 gsm Opt. Envelope Cassette for PFP x 60 - 256 gsm Opt. 2,000 - Sheet Tandem LCF (Pedestal Type) 60 - 256 gsm Opt. 2,000 - Sheet External LCF 60 - 256 gsm Standard Automatic Duplex Unit 60 - 256 gsm
<b>Duplex</b>	Standard Automatic Duplex Unit 60 - 256 gsm
<b>Reproduction Ratio</b>	25% to 400%
<b>Weight</b>	Approx. 57kg
<b>Approx. Dimensions</b>	585 x 586 x 787 mm (W x D x H)
<b>Memory</b>	4GB
<b>Hard Disk Drive</b>	128GB Solid State Drive (SSD)

## e-BRIDGE NEXT PRINT SPECIFICATIONS

<b>PDFL</b>	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
<b>Print Resolution</b>	600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (2 bit) or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
<b>Operating Systems</b>	Windows® 8.1, 10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux®
<b>Network Protocols</b>	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
<b>Printing Protocols</b>	SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP
<b>Print Drivers</b>	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12
<b>Interface</b>	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
<b>Wireless Device</b>	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
<b>Device Management</b>	TopAccess
<b>Account Control</b>	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
<b>Accessibility Features</b>	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist



## Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)\* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication \*Conformance with HCD-PPv1.0 in High Security Mode

**ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65 WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®**

## Environmental Standards Certifications

## SCAN SPECIFICATIONS

<b>Scan Speed</b>	DSDf Scan: Up to 240 ipm Duplex, 120 ipm Simplex (Monochrome or Colour) RADf Scan: Up to 73 ipm (Monochrome or Colour)
<b>Scan Modes</b>	Standard: Full Colour, Auto Colour, Monochrome, Grayscale
<b>OCR</b>	DOC/XLS/PPT/PDF
<b>Scan Resolution</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>File Formats</b>	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX Colour/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX
<b>Image Compression</b>	Colour/Grayscale: JPEG (High, Middle, Low)

## FACSIMILE SPECIFICATIONS

<b>Compatibility</b>	Super G3
<b>Data Compression</b>	MH/MR/MMR/JBIG
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Memory Transmission</b>	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
<b>Scan Speed</b>	0.7 Seconds Per Page, Maximum 73 ipm

## e-FILING SPECIFICATIONS

<b>Operation Method</b>	Colour Touch Screen Control Panel or Client PC
<b>Number of Boxes</b>	1 Public Box, 200 Private User Boxes
<b>Capacity of Boxes</b>	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

## ACCESSORIES (OPTIONS)

### Platen & Document Feeder Options

DSDf	MR4010	Multi-Station Print Enabler	
DSDf with Double Feed Detection	MR4020	Per Seat License	GS1090NODE
RADf	MR3033	e-BRIDGE Plus for OneDrive	
Platen Cover	KA5005PC	for Business V3.0	GB2300NODE

### Additional Paper Options

Paper Feed Pedestal	KD1072	Online V3.0	GB2310NODE
Drawer Module	MY1052	e-BRIDGE Plus for Exchange	
Envelope Cassette Option	MY1053	Online V3.0	GB2320NODE
Large Capacity Feeder	KD1073A4	e-BRIDGE Plus for Gmail	GB2380NODE
External Large Capacity Feeder	MP2002A	e-BRIDGE Plus for Google Workspace	GB2390NODE

### Finishing Options

Inner Finisher	MJ1048	Security SSD (512GB)	GE1280
Multi-Staple Finisher	MJ1113	FIPS HDD (320GB)	GE1260
Saddle-Stitch Finisher	MJ1114	e-BRIDGE Plus Voice Guidance	GB2540NODE
Hole Punch for Inner Finisher	MJ6011	e-BRIDGE Global Print	GB2550NODE
Hole Punch for Console Finisher	MJ6107		

### Miscellaneous Options

Bridge Kit	KN5005	Card Reader Holder	GR1320
Job Separator e-STUDIO3528A	MJ5014	Accessory Tray	GR1330
Job Separator (3528A/4528A)	MJ5015	Panel 10-Key Option	GR1340
<b>Connectivity/Security Options</b>		Work Tray	KK5005
FAX Unit/2 <sup>nd</sup> Line for FAX Unit	GD1370EU	Manual Pocket	KK5008
Wireless LAN/Bluetooth	GN4030A3	Harness for Coin Controller	GQ1280
IP Fax Enabler	GS1100NODE	Accessible Arm	KK2560
2 <sup>nd</sup> NIC Holder	GR1430		
USB Hub	GR1420		
Meta Scan Enabler	GS1010NODE		
IPSec Enabler	GP1080NODE		
Unicode Font Enabler	GS1007NODE		

For more information please contact us:

### Toshiba TEC Singapore Pte Ltd

2 Ang Mo Kio Street 62  
Singapore 569138  
Tel : (65) 6481 9488  
Fax : (65) 6481 2385

Distributed by



TOSHIBA  
Authorized Sole  
Distributor

### INTERNATIONAL OFFICE MACHINES LIMITED

**Corporate Office**  
Ranks Business Centre (3rd Floor), KA 218/1 Pragati Sarani, Kuril, Dhaka 1229.  
Hotline: 09611858585, Tel: 8418523 | Fax: 8417589 | E-mail: info@iomltd.com

### Branches

**Chattoogram**- 6/32, Zilla Parishad Super Market | 01714-168943  
**Bogura**- Saptapadi Market, Bogra | 01711-890615  
**Khulna**- 65, Ahsan Ahmed Road | 01716-749065  
**Sylhet**- 6/03, Karimullah Market, Bandar Bazar | 01711-160285

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation.