TOSHIBA

BV400 Series

Desktop Printers

- The latest print technology incorporated into a sleek case design for ultimate user experience.
- Powerful and scalable system architecture that future-proves your investment.
- A broad set of standard interfaces and optional Wi-Fi or Bluetooth for effortless integration into even the most complex IT environments.
- Optional UHF RFID encoding available for thermal transfer printer versions.





The Ever-Changing Workplace

Delivering reliability to meet future challenges

Every business is unique. That's why Toshiba offers the most reliable print solutions that meet all your labelling requirements, day after day. Toshiba barcode printers provide connectivity and solutions to adapt to the needs of an ever-changing workplace.

To shiba's barcode printers continue to deliver on our promise of Together Information – our commitment to collaborate with clients to provide tailored, cost-effective solutions that meet your evolving workplace needs.

A strong combination of excellent design & advanced connectivity

This most advanced desktop printer series consists of nine different models, all with a small footprint, intelligent design which brings simplicity and efficiency for the ultimate user experience. Enhanced connectivity features enable these printers to be integrated into various networks and, thanks to print language emulations, into almost every print scenario. The robustness of the printer series offers high print quality and performance comparable to mid-ranged printers.

Stylish Design with Outstanding Performance

Designed with the user in mind

A compact footprint was a core criteria in the design of the BV400 desktop printer range. With its ergonomic style and sleek casing these printers suit retail shops, offices or any type of workplace where space is at a premium.

A model to meet every need

With models available in 203 dpi and 300 dpi versions, also available in black or white cabinets, the BV400 series suits to fit into almost any operating environment.

- BV400D direct thermal printers with a compact and stylish design and an increased throughput of up to 7 ips.
- BV420D-GL linerless prints on adhesive labels with no backing paper, reducing waste and keeping the working environment safe and clean.
- BV400T thermal transfer printers enables optional RFID encoding and supports a wide range of ribbons from wax to resin.





Key highlights

- Market leading throughput with up to 7 ips
- · Compact & sleek design with a small footprint
- Intuitive & clear user experience
- Vast print languages & emulations
- RFID encoding available with thermal transfer printers
- SOTI Connect certified for IoT device management

Exceeding Expectations

Ease of use

The integrated LCD screen of the BV410 models provides clear information and notifications alert the user via the colour change of the status LEDs. Changes can be made to the main settings directly on the printer and full printer setup is also available by remote connection.

Future-ready operating system

The redesigned OS platform supports multi print emulations, which enable simple integration into complex IT environments. This platform extends the connectivity and adaptability of the BV400 printers to keep pace with the requirements of an ever-changing workplace.

Speed & efficiency

For printing labels quickly and efficiently the BV400 has market leading print speeds of up to 7 inches per second and an advanced CPU for fast processing of data. With it's rapid boot-time the printer is ready to print from power-on.

Solid reliability

Designed for the most demanding retail environments the renowned reliability of these desktop printers support busy operations – day after day. The optional built-in AC adapters ensure a tidy and safe workplace.

RFID encoding

Toshiba's unique RFID technology is now incorporated into the BV400T desktop printer models, opening a wide-range of new applications across multiple markets. With these new options and an extensive range of features, the BV400 series offers solutions that are usually reserved for industrial printers only.

Linerless printing

The BV420D-GL linerless printer can print on adhesive labels with no backing paper, reducing waste and keeping the working environment safe and clean:

- Toshiba's true label saving technology automatically shortens the length of the label to use only that material that is printed on. This eliminates material waste and saves money.
- With up to 30% more linerless labels per roll you can increase print time, reduce roll changes and lower storage requirements.
- Toshiba linerless labels are completely flexible as they can print to any length of label required without changing the roll.
- Printing on only the length required saves paper and resources and no backing paper means no additional industrial waste.



Specifications BV400D

Direct Thermal Models

White case BV410D-GS02 BV410D-TS02

300 dpi (11.8 dots/mm) Resolution 203 dpi (8 dots/mm) User interface 2x LED, 3x key, with LCD 2x LED, 3x key, with LCD

BV420D-GS02 BV420D-TS02 Black case

203 dpi (8 dots/mm) 3x LED, 2x key 300 dpi (11.8 dots/mm) Resolution

User interface 3x LED, 2x key

Black case linerless BV420D-GL02 Resolution 203 dpi (8 dots/mm) User interface 3x LED, 2x key

General

Print method Direct thermal

Print head Flat head

Dimensions (W x D x H) GS02/TS02 **GL02** 174 x 218 x 173 mm 174 x 288 x 173 mm

GS02/TS02 2.0 kg GL02 2.6 kg Weight

Memory 128 MB (FROM), 128 MB (SRAM)

Operating temperature / GS02/TS02

humidity

5° to 40°C (41° to 104°F) / 5° to 35°C (41° to 95°F) / 25 to 85% 25 to 85%

non-condensing relative non-condensing relative humidity (RH)

humidity (RH)

-20° to 60°C (-40° to 140°F) / 10 to 90% Storage temperature /

humidity

non-condensing relative humidity (RH)

Power supply AC 100 to 240 V, 50/60 Hz

Print

Sensor <u>GS02/TS02</u> Reflective, transmissive GL02 Reflective

GL02 Max. print speed 7 ips (177.8 mm/s) 7 ips (177.8 mm/s)/

5 ips (127 mm/s)

Max. print width GS02/TS02 GL02 108 mm/105.7 mm

Print length

Batch 6-997 mm 17.4-997 mm¹⁾ Cut Peel-off 21.4-148.2 mm¹⁾

Barcodes UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN

128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, POSTNET, RM4SCC, KIX Code, Customer Barcode, GS1 DataBar, USPS Intelligent

2D codes Data Matrix, PDF 417, MaxiCode, QR Code, Micro

PDF 417, Micro QR, GS1 Data Matrix, GS1 QR Code,

Aztec Code

Bitmap font, outline font, price font, optional TTF, Fonts

writable characters

Media

Alignment Centred

Backing paper width GS02/TS02 **GL02** 32 to 102 mm 25.4 to 118 mm

0.06 to 0.19 mm Label thickness

<u>GS02/TS02</u> 25.4, 38.1, 42 mm <u>GL02</u> 38.1 mm Inner media core diameter Standard

Optional 76.2 mm GL02 Max. 107 mm

Outer media roll diameter GS02/TS02 Standard Max. 127 mm Optional Max. 214 mm

Media format Roll, fanfold

Software & connectivity

Emulation ZPL II, DPL, SBPL, EPL2, IPL

Windows 11/10, Windows Server 2019/2016/ Printer driver

2012 R2/2012, SAP, Linux, macOS

Interface USB 2.0, USB Host, Ethernet 10/100 Base T (IPv4 &

IPv6), WLAN 802.11a/b/g/n (dual band for 2.4 GHz/5GHz)¹⁾²⁾, Bluetooth V2.1 EDR with MFi certified¹⁾²⁾,

Language mode TPCL, Basic Command Interpreter (BCI)

Label software BarTender UltraLite, NiceLabel Free

SOTI Connect IoT device

management

Options

For BV400D series Full cutter module³⁾, partial cutter module³⁾, peel-off

module3), serial interface board, wireless LAN module, Bluetooth module, AC adapter cover, external media

stand3

2) Availability varies from country to country

3) Available for GS02/TS02 models only







Specifications BV400T

Thermal Transfer Models

White case BV410T-GS02 BV410T-TS02

Resolution 203 dpi (8 dots/mm) 300 dpi (11.8 dots/mm) User interface 2x LED, 3x key, with LCD 2x LED, 3x key, with LCD

BV420T-GS02 BV420T-TS02 Black case

203 dpi (8 dots/mm) 3x LED, 2x key Resolution 300 dpi (11.8 dots/mm) User interface 3x LED, 2x key

General

Thermal Transfer, direct thermal Print method

Print head Flat head

Dimensions (W x D x H) 200 x 267 x 198.3 mm

Weight 2.9 kg

128 MB (FROM), 128 MB (SRAM) Memory

5° to 40°C (41° to 104°F) / Operating temperature /

humidity

-40° to 60°C (-40° to 140°F) / 10 to 90% Storage temperature /

humidity

non-condensing relative humidity (RH)

25 to 85% non-condensing relative humidity (RH)

Power supply AC 100 to 240 V, 50/60 Hz

Print

Sensor Reflective, transmissive

<u>GS02</u> 7 ips (177.8 mm/s) Max. print speed

TS02 5 ips (127 mm/s)

Max. print width GS02 **TS02** 105.7 mm

Print length

Batch 6-997.9 mm 20.4-997.9 mm¹ Peel-off 21.4-148.4 mm¹⁾

UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN Barcodes

128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, POSTNET, RM4SCC, KIX Code. Customer Barcode, GS1 DataBar, USPS Intelligent

Data Matrix, PDF 417, MaxiCode, QR Code, Micro 2D Codes

PDF 417, Micro QR, GS1 Data Matrix, GS1 QR Code,

Aztec Code

Bitmap font, outline font, price font, optional TTF, **Fonts**

writable characters

Ribbon

Ribbon width 40 to 110 mm

25.4 mm (1"), 12.7 mm (0.5") Ribbon core size

Max. ribbon length 300 m Max. ribbon diameter 65 mm

Media

Alignment Centred Backing paper width 25.4 to 118 mm Label thickness 0.06 to 0.19 mm

Inner media core diameter

25.4, 38.1, 42 mm Standard Optional 76.2 mm

Outer media roll diameter Standard Max. 127 mm Optional Max. 214 mm Media format Roll, fanfold

Software & connectivity

ZPL II, DPL, SBPL, EPL2, IPL **Emulation**

Printer driver Windows 11/10, Windows Server 2019/2016/

2012 R2/2012, SAP, Linux, macOS

Interface USB 2.0, USB Host, Ethernet 10/100 Base T (IPv4 &

IPv6), WLAN 802.11a/b/g/n (dual band for 2.4 GHz/5GHz)¹⁾²⁾, Bluetooth V5.2 BR/EDR with MFi

certified1)2), serial port1)

Language mode TPCL, Basic Command Interpreter (BCI)

BarTender UltraLite, NiceLabel Free Label software

IoT device SOTI Connect management

Options

For BV400T series UHF RFID kit, full cutter module, partial cutter

module, peel-off module, serial interface board, wireless LAN module, Bluetooth module, AC adapter cover, external media stand, print head kits for

resolution change

1) Optional

²⁾ Availability varies from country to country







About Toshiba Tec

To shiba Tec Corporation is a leading provider of information technology, operating across multiple industries - ranging from retail, education and business services to hospitality and manufacturing. With headquarters in Japan and over 70 subsidiaries worldwide, Toshiba Tec Corporation helps organisations transform the way they create, record, share, manage and display information.

For more information please contact us:

Toshiba Tec Corporation 1-11-1, Osaki, Shinagawa-ku, Tokyo 141-8562, Japan

Website www.toshibatec.com

Distributed By:



International Office Machines Limited

Corporate Office

Ranks Business Centre (3rd Floor), KA 218/1 Pragati Sarani, Kuril, Dhaka 1229. Hotline: 09611858585, Tel: 8418523 | Fax: 8417589 | E-mail: info@iomltd.com

Branches

Chattogram- 6/32, Zilla Parishad Super Market | 613705, 01313099099 Bogura- Saptapadi Market, Bogra | 65531, 01711890615 Khulna - 65, Ahsan Ahmed Road | 732372, 01716749065 Sylhet- 6/03, Karimullah Market, Bandar Bazar | 01730-303110 Together Information is Toshiba's vision for how people and organisations create, record, share, manage and display ideas and data.

It is based on our belief that the most successful organisations are those that communicate information in the most efficient way.

We make that possible through an integrated portfolio of industry-specific solutions, all of which reflect Toshiba's commitment to the future of the planet.