



Fanfold or roll media

The CL-S400DT can handle fanfold tickets as well as standard roll media for labels or receipts.

Easy read LCD panel

The LCD panel allows quick and simple configuration and also flashes red when an error occurs quickly alerting the operator.

Environmentally friendly

From production and packaging to utilisation and recycling the CL-S400DT fulfills today's demand for green IT products. The integrated ENERGY STAR® power supply is one of the most efficient at managing power consumption.

CL-S400DT

Label, Ticketing

Applications

- Courier
- Retail
- Logistic / Transport
- Ticketing
- Kiosk
- Betting



Performance ticket and label printing

CITIZEN



With a USB and serial interface on board the CT-S400DT is a future-proof investment. Ethernet and parallel interfaces are available as options.

Specifications

| Model | CL-S400DT |
|------------------------------|--|
| Printing Technology | Direct Thermal |
| Resolution | 203 dpi |
| Print Speed (maximum) | 6 inches per second (150 mm/s) |
| Print Width (maximum) | 4 inches (104 mm) |
| Media Width (min to max) | 0.5 - 4.6 inches (12.5 - 118 mm) |
| Roll Size (max), Core Size | Inside diameter 5 inches (125 mm) External diameter 8 inches (200mm) Core size 1 inch (25mm) |
| Media Thickness (min to max) | 63.5 to 254 μ m |
| Media Length (min to max) | 0.25 to 32 inches (6.35 to 812.8 mm) |
| Media Sensor | Fully adjustable gap, notch and reflective black mark |
| Main Interface | Dual Interface Serial (RS-232C), USB (version 2.0, full speed) |
| Optional interfaces | Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT), Parallel (IEEE 1284 compliant) |
| Mechanism | Hi-Lift™ metal mechanism with wide opening head |
| Control panel | 4 buttons, 16x2 LCD with 2-colour backlight and sophisticated menu configuration system |
| Emulations (Languages) | Datamax® DMX, Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations, Zebra® ZPL2®, CBI™ BASIC Interpreter, Eltron® EPL2® |
| Drivers and software | Free-of-charge from website, including support for various platforms |
| Flash (Non-Volatile Memory) | 8 MB total, 1 MB available for user |
| Size (W x D x H) and Weight | 206 x 149 x 150mm, 2.68 Kg (excluding roll holder) |
| Cutter | Guillotine type, Dealer Installable |

CL-S400DT

Label, Ticketing

Features & Benefits

- Paper load: Durable design - Citizen's proven Hi-Lift™ all-metal mechanism
- Printing Speed: Fast print out - 6 inches per second (150 mm per second)
- Media support: Versatile Media Support - Fanfold media stacks and roll paper support
- Display: 2-colour LCD display enables intuitive operation
- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- Low space requirement - integrated power supply enables clean work station
- ENERGY STAR® compliant
- Small footprint
- Recyclable packaging
- Basic peeler





CITIZEN
Authorized Distributor

INTERNATIONAL OFFICE MACHINES LIMITED

Corporate Office
Ranks Business Centre (3rd Floor), KA 218/1 Pragati Sarani, Kuril, Dhaka 1229.
Hotline: 09611858585; Tel: 8418523 | Fax: 8417589 | E-mail: info@iomltd.com

Branches

Chattogram- 6/32, Zilla Parishad Super Market | 01714-168943
Bogura- Saptapadi Market, Bogra | 01711-890615
Khulna- 65, Ahsan Ahmed Road | 01716-749065
Sylhet- 6/03, Karimullah Market, Bandar Bazar | 01711-160285

CITIZEN SYSTEMS EUROPE GMBH